









































Product Feature Matrix				
	datashur™	diskG	diskashur™	diskashurDT™
AES 256-bit Hardware Encryption				
PIN Activated via onboard keypad				
Wear Resistant keypad				
Epoxy Coating - secured against physical attack				
Brute Force Self Destruct Feature				
Auto-lock on removal from USB				
Supports Admin and User PINs				
Software free				
Capacities	4, 8, 16 GB	250,320,500, 640, 750, 1000 GB	250,320,500, 640, 750, 1000 GB	1000, 2000, 3000 GB
Interface	USB2 *	USB2 *	USB3 *	USB3 *
Physical Size	80 x 20 x 10.5 mm **	120 x 84.5 x 19 mm	120 x 84.5 x 19 mm	182.8 x 114.3 x 38.09 mm
Weight	25 grams	175.7 grams	175.7 grams	1150 grams
Power method	USB Powered	USB powered	USB powered	12VAC Adapter ***
Enclosure type	Extruded Aluminium	Rubberised Plastic	Rubberised Plastic	Extruded Aluminium
Compatibility				
Warranty	3 Years	3 Years	3 Years	3 Years

* All iStorage products operate with USB 1, USB2 & USB3 interfaces

** Dimensions of datashur with sleeve - dimensions of drive without sleeve 78 x 18 x 10.5 mm

*** Supplied with interchangeable heads for UK, Europe, US and Australia